

SOUNDBOND - NC SEALING COMPOUND TO STOP DAMPNESS /LEAKAGES



DESCRIPTION :

Two components Acrylic polymer modified cement based coating to provide waterproof and damproof properties.

ADVANTAGE:

- Suitable for both concrete and masonry to arrest leakage's
- Provides a breathable and aesthetic surface
- Excellent adhesion to the background
- Minimizes crack formation
- Suitable for both vertical & horizontal surface
- Seamless finish
- Suitable to plaster or screed over

AREA OF APPLICATION:

Soundbond – NC can be used as a waterproofing coating in basement walls, ceiling, floors, underground shafts, fountains, retaining walls and other areas where such application is required.

MIXING APPLICATION:

Background where Soundbond – NC to be applied should be thoroughly cleaned with water or wirebrush. Mix using a mechanical mixer 23 Kg of Soundbond- NC powder with 4 Ltrs liquids provided along & clean potable water to achieve a brushable slurry. Using a clean brush apply evenly onto the background in a single coat. Additional coats cab be applied after 8 to 10 hrs depending upon the conditions. The mix already prepared should be used with 30 minutes. Do not apply on overwet surfaces. Before applying any decorative coatings Soundbond – NC should be allowed to dry between 5 to 7 days. Protect from direct sunlight for 72 hrs.



DENSITY: 1.85 kg per Ltr.

COMPOSITION / COVERAGE:

1.2 to 1.65 kg per M2 depending on the requirement and background condition.

PACKING:

23 kg dry powder in HDPE bag with liner and 4 Ltrs liquid in cans.

STORAGE:

Can be stored under shaded dry condition for a period of 6 months.

WARRANTY:

If applied as per the recommendation in the product data-sheet, Sound bond - NC is guaranteed for the purpose of which it is recommended. We can not assume responsibility of misuse of our products. We assume no responsibility for the finished work as we have no control over factors such as mixing, application, background preparation, whether and other condition that may prevail at the time of applications.



SOUND BUILD CARE PVT. LTD.

Regd Off: Unit No. 13, Swastik Chamber, Ground Floor, C.S.T. Road Chembur, Mumbai 400071

TEL : 022-25236991/92 . **FAX:** 022-25236995

Email: info@soundbuildcare.com

www.soundbuildcare.com

DISCLAIMER :

If applied as per the recommendation in the product data-sheet, PMC-1 is guaranteed for the purpose of which it is recommended . We can not assume responsibility of misuse of our products . We assume no responsibility for the finished work as we have no control over factors such as mixing, application surface preparation, weather and other conditions that may prevail at the time of applications.