

SOUNDBOND - SBR LATEX BONDING AGENT



DESCRIPTION :

A styrene butadiene latex emulsion to modify for all kinds of cement based materials such as floor screed mortar etc.

PROPERTIES:

Enhances the performance of concrete and mortar to increase the waterproofing properties, to reduce permeability, to minimize corrosion, to increase durability.

AREA OF APPLICATION:

To repair damaged concrete, to prepare water proof plasters and mortars, to water proof tanks and basements.

APPLICATION:

The background should be thoroughly cleaned before the application of bonding slurry. Mix one part of cement with one part of SBR to prepare the bonding slurry. Prepare the repair mortar with 50 kg of cement | 30 kg of clean dry sand with 5 Ltr of SBR and sufficient amount of water to achieve a workable consistency. Apply the slurry on to the prepared background followed by the repair mortar as the slurry sets rapidly. Please ensure good compaction of the mortar.



SOUND BUILD CARE PVT. LTD.

CHARACTERISTICS:

Colour / Form	=	White liquid
Specific gravity	=	1.01
Solubility	=	Water soluble
Toxicity	=	Non-toxic.

CONSUMPTION / COVERAGE:

Slurry 30 Sq. Ft per Ltr
Modified mortar 100 Sq. Ft at 10 MM thick (This is only a guide & actual will be as per site conditions)

PACKING: 5, 30 Ltrs.

STORAGE:

Can be stored upto 6 months in original container under shaded and dry condition.

WARRANTY:

If applied as per the recommendation in the product data-sheet, Sound bond – SBR is guaranteed for the purpose of which it is recommended. We can not assume responsibility of misuse of our products. We assume no responsibility for the finished work as we have no control over factors such as mixing, application, background preparation, whether and other condition that may prevail at the time of applications.



SOUND BUILD CARE PVT. LTD.

Regd Off: Unit No. 13, Swastik Chamber, Ground Floor, C.S.T. Road Chembur, Mumbai 400071

TEL : 022-25236991/92 . **FAX:** 022-25236995

Email: info@soundbuildcare.com

www.soundbuildcare.com

DISCLAIMER :

If applied as per the recommendation in the product data-sheet, PMC-1 is guaranteed for the purpose of which it is recommended . We can not assume responsibility of misuse of our products . We assume no responsibility for the finished work as we have no control over factors such as mixing, application surface preparation, weather and other conditions that may prevail at the time of applications.