

# SOUNDFLOOR - HT CARBORANDUM BASED HARDTOP



## DESCRIPTION:

Soundfloor – HT is non metallic surface hardener. Very high abrasion resistant, dry shake hardener.

## COMPOSITION:

A blend of high quality portland cement specially selected aggregates and chemical additives.

## PROPERTIES / USAGE:

High wear and abrasion resistant, non-slip, resistance to oil, water proof, extremely hard wearing, easy to clean, minimum maintenance required, stain free, monolithic application. Suitable for industrial and commercial use where maintenance is not required. Increases the abrasion resistance of concrete by 200%.

## APPLICATION:

Please ensure the freshly laid concrete has the initial set. Inundation should not be more than 2 to 3 MM. There should not be any free water on the surface. Application of Soundfloor – HT to be carried out into two stages.

STAGE – 1 : 50% of the total quantity required for an area should be evenly sprinkle on the surface. After few minutes when the surface become uniform gently trowel. Please do not overwork the surface other wise the powder will be buried.

STAGE – 2 : Distribute evenly the remaining material onto the surface but at a right angle to the initial application and float as before. Final finishing can be achieved by conventional method or by power floating.



**SOUND BUILD CARE PVT. LTD.**

## CONSUMPTION:

Consumption depends on the intended traffic. Please use the following as a guide.

Light 2.5 to 3 kg per M2

Medium 5 to 6 kg per M2

Heavy 7 to 8 kg per M2

## CURING:

Curing is absolutely essential either with water or with other means.

## PACKING:

Available in 25 kg HDPE bags.

## STORAGE:

Can be stored under shaded dry condition for a period of 12 months.

## WARRANTY:

If applied as per the recommendation in the product data-sheet, Soundfloor – HT is guaranteed for the purpose of which it is recommended . We can not assume responsibility of misuse of our products . we assume no responsibility for the finished work as we have no control over factors such as mixing, application, background preparation, whether and other condition that may prevail at the time of applications.



**SOUND BUILD CARE PVT. LTD.**

**Regd Off:** Unit No. 13, Swastik Chamber, Ground Floor, C.S.T. Road Chembur, Mumbai 400071

**TEL :** 022-25236991/92 . **FAX:** 022-25236995

**Email:** info@soundbuildcare.com

**www.soundbuildcare.com**

### DISCLAIMER :

If applied as per the recommendation in the product data-sheet, PMC-1 is guaranteed for the purpose of which it is recommended . We can not assume responsibility of misuse of our products . We assume no responsibility for the finished work as we have no control over factors such as mixing, application surface preparation, weather and other conditions that may prevail at the time of applications.