



SOUNDAID - PB

LIQUID BONDING AGENT FOR PLASTER



Description

High polymer modified bonding agent for new & old concrete and as a plastering aid.

Properties

Easy to apply, economical, excellent bonding properties, eliminates the hardship of hacking the concrete surface, and non-toxic.

Area of Application

For bonding of plaster on to concrete and new concrete to old concrete etc.

Consumption / Coverage

8 to 10 Sq. M2 per Ltr

Packing

5, 20 , 30 & 200 Ltrs .

Application

The background where Soundaid - PB is to be applied should be thoroughly cleaned to remove any dust and other contamination and should be washed down with clean potable water. Once the background is dry, apply Soundbond - PB without any dilution uniformly using a brush or a suitable spray equipment in order to obtain a uniform thin film. Please ensure the entire surface is covered entirely with Soundbond - PB. Apply fresh concrete or plaster wet on wet with the background. The normal waiting period 45 minutes to 1 hour to depending upon the temperature, windvelocity etc.

Storage

Can be stored upto 6 months in original container under shaded and dry condition

Technical Assistance

The technical team at Sound Build Care Pvt Ltd. is ready to assist you anytime in case of any technical queries

Warranty

If applied as per the recommendation in the product data-sheet, SOUNDAID - PB is guaranteed for the purpose of which it is recommended. We can not assume responsibility for misuse of our products. We assume no responsibility for the finished work as we have no control over factors such as mixing, application, background preparation, weather and other condition that may prevail at the time of applications.

SOUND BUILDCARE PVT. LTD.

Manufacturers of Building Construction Products

HEAD OFFICE

 13, Swastik Chamber, CST Road, Chembur, Mumbai 400 071, India.

 91-22-25236993 | +91 9137766817

 www.soundbuildcare.com  info@soundbuildcare.com