



SOUNDBOND AR

ACRYLIC BONDING AGENT

Description

Soundbond AR is an Acrylic emulsion bonding agent to provide improved bonding properties.

Properties

It provides greater additions, reduces porosity, and increases the strength, highly economical.

Area of Application

Recommended to use as priming & bonding coat for SBC's repair material and screed. Also suitable for all types of concrete and mortars.

Direction for Use

As a primer, mix one part Soundbond - AR with three parts of water and apply on to the clean prepared background using a brush to cover the entire area. After approximately 6 to 8 hrs mix one part of Soundbond - AR with one part water and apply as a bonding coat on the primed surface. Apply mortar or concrete on to the bonding coat wet on wet.

Consumption / Coverage

5 to 8 Sq.m per ltr

Packing

5 ltrs., 20 ltrs., 200 ltrs.

Storage

Can be stored upto 1 year in original container under shaded and dry condition.

Technical Assistance

The technical team at Sound Build Care Pvt Ltd. is ready to assist you anytime in case of any technical queries

Warranty

If applied as per the recommendation in the product data-sheet, SOUNDBOND AR is guaranteed for the purpose of which it is recommended. We can not assume responsibility for misuse of our products. We assume no responsibility for the finished work as we have no control over factors such as mixing, application, background preparation, weather and other condition that may prevail at the time of applications.

SOUND BUILDCARE PVT. LTD.

Manufacturers of Building Construction Products

HEAD OFFICE

 13, Swastik Chamber, CST Road, Chembur, Mumbai 400 071, India.

 91-22-25236993 | +91 9137766817

 www.soundbuildcare.com  info@soundbuildcare.com