

SOUNDFLOOR - HT

CARBORANDUM BASED HARDTOP

Description

Soundfloor - HT is non metalic suraface hardener. Very high abrasion resistant, dry shake hardener.

Composition

A blend of high quality portland cement, specially selected aggregates, and chemical additives.

Properties / Usage

High wear and abrasion resistant, non-slip, resistance to oil, water proof, extremely hard wearing, easy to clean, minimum maintenance required, stain free, monolithick application. Suitable for industrial and commercial use where maintenance is not required. Increases the abrasion resistance of concrete by 200%.

Application

Please ensure the freshly laid concrete has the initial set. Inundation should not be more than 2 to 3 MM. There should not be any free water on the surface. Application of Soundfloor - HT to be carried out into two stages.

STAGE - 1: 50% of the total quantity required for an area should be evenly sprinkle on the surface. After few minutes when the surface become uniform gently trowel. Please do not overwork the surface other wise the powder will be buried.

STAGE - 2: Distribute evenly the remaining material onto the surface but at a right angle to the initial application and float as before. Final finishing can be achieved by conventional method or by power floating.

Consumption

Consumption depends on the intended traffic. Please use the following as a guide. Light 2.5 to 3 kg per M2 Medium 5 to 6 kg per M2 Heavy 7 to 8 kg per M2

Curing

Curing 7 days is absolutely essential either with water or with other means.

Packing

Available in 25 kg HDPE bags.

Storage

Can be stored under shaded dry condition for a period of 12 months.

Technical Assistance

The technical team at Sound Build Care Pvt Ltd. is ready to assist you anytime in case of any technical queries

Warranty

If applied as per the recommendation in the product data-sheet, SOUNDFLOOR – HT is guaranteed for the purpose of which it is recommended. We can not assume responsibility for misuse of our products. We assume no responsibility for the finished work as we have no control over factors such as mixing, application, background preparation, weather and other condition that may prevail at the time of applications.

SOUND BUILDCARE PVT. LTD.

Manufacturers of Building Construction Products

HEAD OFFICE

🕈 13, Swastik Chamber, CST Road, Chembur, Mumbai 400 071, India.

91-22-25236993 | +91 9137766817